

FUEL TANK LINER KIT INSTRUCTIONS

Directions for using Northern's Fuel Tank Liner Kit in 3 Easy Steps



STEP ONE: Fuel Tank Cleaner

Cleaning and defuming the tank: Pour the quart of Tank Cleaner into the emptied tank. Slosh to cover all surfaces. Allow to soak for 15 minutes. Drain and rinse with water several times to be sure no detergent residue remains. Remember, a few extra minutes of cleaning will let the chemical work so please be patient for the best results. Do not get on to skin or clothing. Be sure to wear gloves and eye protection goggles. Allow tank to dry thoroughly on the inside before proceeding.

NOTE: Northern Tank Prep is a solvent of most paints. Please take precautions to avoid Tank Prep contact with the exterior of your painted tank or any other painted surface.



STEP TWO: Fuel Tank Prep

Prep: Pour half of the quart of Tank Prep into the tank, slosh it around thoroughly and pour into a pail. Pour the remainder of the Tank Prep into the tank and repeat. Once you have done this and your tank is dry, you are ready for the Fuel Tank Liner.



STEP THREE: Fuel Tank Liner

Lining the tank: Pour the desired amount of Northern Fuel Tank Liner into the tank. Roll the tank around to cover the area you wish to seal. Pour excess Fuel Tank Liner back into the can. Let tank stand up-side down so any excess Fuel Tank Liner drains out and thoroughly dries. Do not let the excess Fuel Tank Liner "pool" in the tank. Remember, the better job done coating the tank with Fuel Tank Liner, the better the finished product will be.